



SPECIFICATIONS



General Traffic Equipment

RELIABLE

Advanced electronics offers minimum power consumption and long unattended life. Most adjustments can be made without opening the case. The rugged case shields the components against the elements and the heavy duty locking swivel arm protects connecting cables from vandalism

INTELLIGENT

Dynamic Proportional Volume Compensation monitors ambient noise level and adjusts output to ensure audibility of signal. Normally preset to +5 dB above ambient noise

NOISE FRIENDLY

Sound Inhibit (optional) allows the audible signal to be disabled at sensitive periods, during complex traffic phases, or as required. **Button Actuated Time (BAT)** (optional) generates WALK sounds only when needed. Holding the WALK button down for 3 seconds (duration is adjustable) actuates the audible signal to trigger with the WALK visual signal.

CUSTOMIZED MESSAGES

Play customized messages or sounds up to 15 seconds long. Directly recordable into DS100 or Factory Programmed

Please specify powder coated finish when ordering



OUTPUTS

"Cuckoo" - North/South. Electronic bird chirping by method of two (2) combined frequencies.

Duration 0.6 seconds +/- 20%
Frequency Base 1,100 Hz +/- 20%
Frequency Deviation +120 Hz +/- 20%

"Peep-Peep" - East/West. Electronic bird chirping by method of continuous variation.

Duration 0.2 seconds +/- 20%
Frequency Base 2,800 Hz +/- 20%
Frequency Deviation -800 Hz +/- 20%

Transient Protection Common mode; fuse
Warranty: 2 years

Certification: Warnock Hersey approved to CSA C22.2

DIMENSIONS

Size 5" H x 3.75" W x 5" D
(127 x 95 x 127 mm)

Weight 3 lb (1.36 kg)

Power Requirements 115 VAC +/- 20%
60 Hz, 3 watts

Humidity Range 5-95% relative humidity

Temp. Range -35° to 165° F
-37° to 73° C

Output 90 db @ 1 watt / 1 meter
(self switching to one of two adjustable output levels depending on ambient noise conditions)

www.generaltrafficequip.com