

SIGNAL HARDWARE

Wire Entrance Head - Aluminum



- *Female Type Designation.*
- *Cast from Die-Cast Aluminum Alloy #413.*
- *Stainless Steel Bushings in All Pivot Holes.*
- *Five Hole Pin Adjustment.*
- *Large Wire Throat Opening.*
- *Precision CNC Machined Threads.*
- *Integrally Cast Serrated Ring.*
- *Dual Setscrews for Locking.*
- *Head Width is 5/8"*
- *Choice of Powder-Coated Finishes.*



Please specify powder-coated finish when ordering.



General Traffic has corrected the flaws of the existing wire entrance "goosenecks" being sold by our competitors and we present our version, WE-750F, for your review. Durable, die cast aluminum is used in the casting construction for many years of worry-free service in the field. A job-designed "sweeping" wireway throat will enable electricians quicker installations. Interior threads are typically 1 1/2" - 1 1/2 NPSM (Gaged for tolerance).



**General
Traffic
Equipment
Corporation**

259 Broadway, Newburgh, NY 12550

(845) 569-9000

TOLL FREE:

(800) 222-2828

FAX:

(845) 569-1800

EMAIL:

info@generaltrafficequip.com

www.generaltrafficequip.com

General Traffic Equipment